

LANDAUER®

Now offering a Real-time dose measurement system featuring RaySafe i3



Powered by  RaySafe™



- Radiation exposure from medical procedures has increased dramatically in the United States since 1980
- Interventional cardiologists receive the highest amounts of radiation among medical personnel
- Radiation exposure can be reduced significantly by optimizing behavior and by using protective devices



## The LANDAUER Real-time dose measurement system powered by RaySafe i3 builds a better Radiation Safety Culture™

RaySafe i3 visualizes X-ray exposure in real-time using easy-to-read bar graphs. Instant feedback empowers medical staff to learn and adapt their behavior to minimize unnecessary radiation exposure.

The measurements are simultaneously stored for post-procedure analysis to facilitate continued learning as well as to enable comparisons over time or between labs.

# The RaySafe i3 Data Transfer Overview



## Real-time Dosimeter

The Real-time Dosimeter measures and records radiation every second. Data is transferred wirelessly to the Real-time Display. A hidden USB connector connects the Real-time Dosimeter to the Dose Viewer software, which can be used to change settings and to view and export dose data.

It is easy to wear, requires minimal maintenance and is made to be personalized.

## Real-time Display

The Real-time Display shows dose data for connected dosimeters in real-time. Green, yellow and red bars indicate the dose rate for each individual user; accumulated dose is displayed next to the bars. By tapping a name, more detailed information about that person's dose history can be accessed.



## Software

Dose Viewer is used for administrating dosimeters and viewing personal dose information. For advanced analysis, reporting and archiving of dose information, use Dose Manager. It manages multiple dosimeters and can retrieve dose information from multiple Real-time Displays throughout the hospital network or via USB storage.



# ABCs for a Radiation Safety Culture™

## A Avoidance

Protective clothing and devices, such as lead aprons, thyroid collars, glasses, ceiling suspended screens and table-mounted lead curtains, are the first line of defense against radiation exposure. Personal dosimeters are used to monitor and help regulate exposure.


## B Behavior


Your behavior will affect your radiation exposure. When feasible, increase your distance and decrease the exposure time. Scatter radiation is typically lower on the detector side.

In addition, ensure that the proper equipment and appropriate techniques are used, including collimating the X-ray beam.

## C Control

Ultimately, controlling your dose results from knowing your dose. Only an active dosimeter such as RaySafe i3 provides constant, real-time radiation exposure information. With this visible information you can take action to reduce your dose.





SCATTERED RADIATION




“The improvement in radiation protection has been more than dramatic at the URM. There is no substitute for a constant and real-time reminder of the dose being received.”

*Labib H. Syed, M.D., M.P.H.*  
*University of Rochester Medical Center*

“We feel better about our work and our safety. Now that we see what RaySafe real-time dosimetry does for us, we wouldn’t want to work at a place that doesn’t have it.”

*Dawn Dowling, Technologist*  
*Lawrence General Hospital*

# RaySafe i3 Data Transfer Overview



# Selected Specifications

## DOSIMETER


<b>WEIGHT</b>	34 g (1.20 oz)
<b>DIMENSIONS</b>	40 × 58 × 17 mm 1.6 × 2.3 × 0.7 in
<b>OPERATIONAL QUANTITY</b>	H <sub>p</sub> (10)
<b>ENERGY DEPENDENCE</b>	< 25% (N-series, 40 – 150 kV)
<b>TEMPERATURE DEPENDENCE</b>	< 5% (18 °C – 26 °C) < 25% (15 °C – 18 °C, 26 °C – 35 °C)
<b>RESPONSE TIME</b>	< 1 s, above 100 μSv/h < 5 s, below 100 μSv/h
<b>INTEGRATION INTERVAL</b>	1 s
<b>DETECTION LIMIT</b>	< 30μSv/h
<b>DOSE RATE UNCERTAINTY (CONTINUOUS RADIATION)</b>	10% or 10μSv/h (40 μSv/h – 150 mSv/h) 20% (150 mSv/h – 300 mSv/h) 40% (300 mSv/h – 500 mSv/h) The measured dose rate is monotonically increasing up to 1 Sv/h.
<b>DOSE REPRODUCIBILITY</b>	10% or 1 μSv
<b>MAXIMUM LIFETIME DOSE</b>	10 Sv
<b>BATTERY</b>	CR2450 (replaceable, 1 – 2 years lifetime depending on usage)
<b>COMMUNICATION</b>	Radio communication to real-time display, carrier frequency depending on region. USB port for connection to PC

## REAL-TIME DISPLAY


<b>DOSE UNIT</b>	Sv or rem
<b>DIMENSIONS</b>	300 × 250 × 60 mm 11.8 × 9.8 × 2.4 in
<b>WEIGHT</b>	1 240 g (43.74 oz)
<b>DISPLAY</b>	10.4" touch screen
<b>STORAGE</b>	Dose rate by second and accumulated dose by hour for connected dosimeters. For 50 dosimeters the memory size allows storage of up to 5 years of accumulated dose and dose rate for the last 250 hours of exposure each.
<b>INTERFACES</b>	Ethernet connection for Dose Manager USB connection for synchronizing data to USB memory stick
<b>POWER</b>	12 V DC, <1.5 A External power supply included
<b>SOFTWARE REQUIREMENTS</b>	
<b>OPERATING SYSTEM</b>	Windows XP, Vista, 7, 8 or 10
<b>SYSTEM MEMORY</b>	At least 1 GB (Dose Viewer) At least 2 GB (Dose Manager)
<b>USB CONNECTION</b>	1 × USB 2.0
<b>HARD DRIVE</b>	At least 15 GB available space (Dose Manager)

Instrument specifications are subject to purchased configuration. All specifications may change without notice.

TYPICAL ANGULAR RESPONSE (RELATIVE TO 0°)



TYPICAL ENERGY RESPONSE





## Like a canary in a coal mine

In the early days of coal mining, canaries were used as warning systems. If the little yellow bird stopped singing, the miners knew that the level of dangerous gases had substantially increased and it was time to exit the mine.

In the operating room, RaySafe i3 is the modern-day canary. By providing real-time, accurate and easy-to-interpret dose information, RaySafe i3 helps healthcare workers decide when it is time to adjust their working behavior to avoid unnecessary exposure.

Learn More

Visit [landauer.com/real-time-dosimetry](https://landauer.com/real-time-dosimetry)